

Omron Adept Hornet 565



The Hornet 565 is a parallel robot for high-speed picking and packaging applications. The powerful controls are fully embedded into the base of the robot, saving valuable floor space and reducing installation costs and complexity. The Hornet 565 features a hygienic design that minimizes contamination risks, including a standard IP65 rating and corrosion resistant materials for easy wash down. The Hornet is part of Adept's complete robotic packaging solution that includes integrated high-speed conveyor tracking, powerful vision guidance, and easy-to-use application software created specifically for the packaging market. The robot can also be programmed directly from a PLC, minimizing training and deployment time by using familiar ladder logic programming languages (IEC 61131-3).

Product Features

- Up to 50% less floor space required
- Up to 25% larger volume workspace than similar sized robots
- Up to 50% lighter for easy overhead installation
- Up to 25% faster with equivalent payloads
- Up to 30% more repeatable at equivalent conveyor speeds

Product Benefits

- > Hornet 565 requires no external control electronics, with all amplifiers and controls fully embedded into the robot
- > Extended vertical reach allows for a 0.36 m³ (12.7 ft³) workspace, enabling a wider variety of packages to be used. See diagram on reverse for details
- > 52kg (115lbs) total weight simplifies overhead installation
- > 0.32 s cycle time enables higher product throughput and reduces cost per pick
- > Industry-leading conveyor tracking capabilities allow for <5mm repeatability at all conveyor speeds (pending)

Specifications

Number of Axes	3 or 4	
Mounting	Inverted	
Payload		
Rated	1 kg	
Max.	3 kg	
Working Range		
Diameter	1130 mm	
Height	425 mm	
Rotation	0° (3 axis) ± 360° (4 axis)	
Repeatability	± 0.10 mm (Uni-directional)	
Robot Cycle Times, sustained (seconds, at 20°C ambient)		
Payload	4 axis*	3 axis*
0.1 kg	0.35	0.32
1.0 kg	0.37	0.34
3.0 kg	0.42	0.38
* Adept Cycle, in mm (25/305/25)		
Power Requirements		
24 VDC : 6 A		
200 to 240 V AC : 10 A, single-phase		
Power Consumption for 25/305/25 mm cycle		
1.0 kg	0.260 kW	
Conveyor Tracking		
Conveyor Speed (mm/s)	Repeatability (mm)	
200	0.5	
350-750	0.5	
800-1400	3.0	
Protection		
Below mounting points: IP65		
Above mounting points: IP40 (with optional IP65 cable sealing kit)		
Environmental Requirements		
Ambient Temperature	1 - 40 °C	
Humidity Range	5 - 90 % (non-condensing)	
Weight	52 kg (115 lbs)	
CE Compliant		

Dimensions: Omron Adept Hornet (mm)



- The Omron Adept Hornet system includes the following:

- Hornet 565 robot with fully integrated amplifiers and controls
- Cable to connect optional front panel, pendant, and external safety systems
- Adept ACE™ software - an integrated, point-and-click development environment for Adept's entire product portfolio of robots and controls
- User documentation

Downloads:

Omron Adept Technologies, Inc.

Tel: 925-245-3400 Email: info@adept.com

omron247.com

Specifications subject to change without notice.

©2016 Omron. ALL RIGHTS RESERVED.

Pub Number R67I-E-01

09366-073 Rev. A